pH/EC/TDS رنج بالا هانا HI991301

مولتی پارامتر HI991301 با اندازه گیری رنج ۰ تا ۲۰ mS برای ارائه pH ، کانداکتیویتی ، مواد جامد محلول کل و اندازه گیری دما طراحی شده است.

HI991301دستگاهی ضد آب ، پرتابل و سبک است.

پراب مولتی پارامتر HI 1288 از پیش تقویت شده دارای یک سنسور تمیز کردن آسان و یک اتصال پارچه ای است که می تواند برای افزایش عمر پراب بیشتر کشیده شود.

این مدل دارای کالیبراسیون خودکار یک یا دو نقطه ای است.

نمایشگر LCD چند سطح کنتورها همزمان با دمای جریان اندازه گیری جریان را نشان می دهند.

پیام های آموزشی روی صفحه برای کالیبراسیون و تنظیمات وجود دارد .

دارای جبران خودکار دما می باشد.

pH، EC / TDSو دما را با یک پراب اندازه گیری کنید.

مشخصات فنی pH/EC/TDS رنج بالا هانا HI991301

Range	pH	0.00 to 14.00 pH
	EC	0.00 to 20.00 mS/cm
	TDS	0.00 to 10.00 ppt (g/L)
	Temperature	0.0 to 60.0°C (32.0 to 140.0°F)
Resolution	pH	0.01 pH
	EC	0.01 mS/cm
	TDS	0.01 ppt
	Temperature	0.1°C (0.1°F)

Accuracy	pH	±0.01 pH
	EC	±2% F.S.
	TDS	±2% F.S.
	Temperature	±0.5°C (±1.0°F)
TDS Conversion Factor		selectable 0.45 to 1.00 with 0.01 increments (default 0.50)
pH Calibration		automatic, one or two point calibration with two sets of memorized buffers (Standard 4.01, 7.01, 10.01 or NIST 4.01, 6.86, 9.18)
EC/TDS Calibration		automatic, 1 point at 6.44 ppt (CONV 0.5) at 9.02 ppt (CONV 0.7) at 12880 µS/cm (others)
Temperature Compensation	pH	Automatic
	EC/TDS	Automatic with selectable ß from 0.0 to 2.4%/°C with 0.1 increments
Probe		HI 1288 PVC body, pre-amplified multiparameter probe with internal temperature sensor, DIN connector and 1.2 m (3.93') cable (included)
Battery Type / Life		1.5V AAA (3) /approximately 500 hours of continuous use. auto-off after 8 minutes of inactivity
Environment		0 to 50°C (32 to 122°F); RH max 100%
Dimensions		152 x 58 x 30 mm (6.0 x 2.3 x 1.2")
Weight		205 g (7.2 oz.)